

PHONE: (303)442-1255 • FAX: (303)449-5274 • E-MAIL: itl@itlboulder.com • WEBSITE: www.itlboulder.com
REPORT NUMBER: ITL63762

DATE: 12/29/09
REVISED: 02/01/10

PAGE 1

PREPARED FOR: B-K LIGHTING, INC.

CATALOG NUMBER: NS-LED-e23-NSP-12; AR-LED-TR-e23-NSP-12-C; AR-LED-RM-e23-NSP-12-C;
DS-LED-e23-NSP-12; RM-LED-e23-NSP-12-C; SN-LED-e23-NSP-12-C;
ST-LED-e23-NSP-12-C; SF-LED-e23-NSP-12-C; TF-LED-e23-NSP-12-C;
WS-LED-e23-NSP-12; AW-LED-e23-NSP-12; SW-LED-e23-NSP-12; VS-LED-e23-NSP-12;
VQ-LED-e23-NSP-12; GD-LED-e23-NSP-12; GQ-LED-e23-NSP-12; EC-LED-e23-NSP-12;
ED-LED-e23-NSP-12; SM-AR-LED-e23-NSP-12-C

LUMINAIRE: MACHINED CYLINDRICAL METAL HOUSING, ONE CIRCUIT BOARD WITH 3 LEDS, ONE CLEAR CONICAL PLASTIC OPTIC PER LED, MOLDED BLACK PLASTIC OPTIC MOUNTING FRAME, CLEAR FLAT MICRO-PRISMATIC GLASS LENS IN MACHINED WHITE PAINTED CYLINDRICAL METAL FRAME WITH UNFINISHED INTERIOR, LENS PRISMS IN.

LAMPS: THREE 2.5-WATT WHITE LIGHT EMITTING DIODES (LEDs) EACH WITH CLEAR HEMISPHERICAL INTEGRAL PLASTIC LENS, LEDS AIMED AT THE HORIZON.

TOTAL INPUT WATTS = 8.2 AT 12.0 VOLTS

LED DRIVER: INTEGRAL


NOTE: DATA SHOWN IS ABSOLUTE FOR THE SAMPLE PROVIDED AT RATED INPUT VOLTAGE (12VAC, 60Hz) TO THE LED DRIVER. LAMP INFORMATION PROVIDED BY CLIENT.

TEST PROCEDURE: IESNA LM-79-08

TEST DISTANCE = 25.25 FEET

FLOODLIGHT CHARACTERISTICS


IES TYPE	3H X 3V	AT	0.0 H,	0.0 V	AXIAL CANDLEPOWER			
					DEG	HORIZ.	DEG	VERT.
MAXIMUM CANDLEPOWER	3594.							
HORIZONTAL BEAM ANGLE (50%)	17.6	deg						
VERTICAL BEAM ANGLE (50%)	14.1	deg						
HORIZONTAL FIELD ANGLE (10%)	33.0	deg						
VERTICAL FIELD ANGLE (10%)	31.4	deg						
BEAM LUMENS (% FIXTURE)	143.	(39.1 %)			90.0	0.	90.0	0.
FIELD LUMENS (% FIXTURE)	301.	(82.3 %)			85.0	0.	85.0	0.
TOTAL LUMENS (% FIXTURE)	365.	(100.0 %)			75.0	0.	75.0	0.
EFFICACY = 44.5 Lm/W					65.0	1.	65.0	1.
					55.0	3.	55.0	2.
					47.5	4.	47.5	3.
					42.5	6.	42.5	5.
					37.5	9.	37.5	8.
					33.0	13.	33.0	13.
					29.0	20.	29.0	21.
					25.5	31.	25.5	36.
					22.5	56.	22.5	71.
					19.5	140.	19.5	157.
					17.0	303.	17.0	280.
					15.0	527.	15.0	422.
					13.0	859.	13.0	607.
					11.0	1281.	11.0	866.
					9.0	1746.	9.0	1258.
					7.0	2253.	7.0	1759.
					5.0	2779.	5.0	2382.
					3.0	3252.	3.0	3014.
					1.0	3552.	1.0	3513.
					0.0	3594.	0.0	3594.
					-1.0	3552.	-1.0	3552.
					-3.0	3252.	-3.0	3146.
					-5.0	2779.	-5.0	2503.
					-7.0	2253.	-7.0	1853.
					-9.0	1746.	-9.0	1301.
					-11.0	1281.	-11.0	904.
					-13.0	859.	-13.0	617.
					-15.0	527.	-15.0	401.
					-17.0	303.	-17.0	252.
					-19.5	140.	-19.5	135.
					-22.5	56.	-22.5	65.
					-25.5	31.	-25.5	35.
					-29.0	20.	-29.0	21.
					-33.0	13.	-33.0	13.
					-37.5	9.	-37.5	9.
					-42.5	6.	-42.5	5.
					-47.5	4.	-47.5	3.
					-55.0	3.	-55.0	2.
					-65.0	1.	-65.0	1.
					-75.0	0.	-75.0	0.
					-85.0	0.	-85.0	0.
					-90.0	0.	-90.0	0.



Checked *N. WHITE*
Approved *R. BEATTIE*

ALL CANDELA AND LUMEN VALUES IN THIS REPORT ARE BASED ON ABSOLUTE PHOTOMETRY.

THIS REPORT IS BASED ON PUBLISHED INDUSTRY PROCEDURES. FIELD PERFORMANCE MAY DIFFER FROM LABORATORY PERFORMANCE.



itl boulder
 THE LIGHT CENTER OF THE INDUSTRY SINCE 1955

INDEPENDENT TESTING LABORATORIES, INC.
 3386 LONGHORN ROAD, BOULDER, CO 80302 USA

PHONE: (303)442-1255 • FAX: (303)449-5274 • E-MAIL: itl@itlboulder.com • WEBSITE: www.itlboulder.com

REPORT NUMBER: ITL63762
 PREPARED FOR: B-K LIGHTING, INC.

DATE: 12/29/09
 REVISED: 02/01/10

CANDELA TABULATION

AVERAGE OF RIGHT AND LEFT SIDES

	0.0	1.0	3.0	5.0	7.0	9.0	11.0	13.0	15.0	17.0	19.5	22.5	25.5	29.0	33.0	37.5	42.5	47.5	55.0	65.0	75.0	85.0	90.0
90.0	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.
85.0	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.
75.0	0.	0.	1.	0.	1.	1.	0.	1.	1.	0.	0.	0.	0.	1.	0.	0.	0.	0.	0.	0.	0.	0.	0.
65.0	1.	2.	1.	1.	2.	1.	1.	1.	2.	1.	1.	1.	1.	1.	1.	1.	1.	0.	0.	0.	0.	0.	0.
55.0	2.	3.	2.	2.	3.	2.	2.	3.	2.	2.	2.	2.	2.	2.	2.	1.	1.	1.	1.	0.	0.	0.	0.
47.5	3.	4.	4.	4.	4.	4.	4.	4.	4.	4.	4.	3.	3.	3.	2.	2.	2.	1.	1.	0.	0.	0.	0.
42.5	5.	6.	5.	6.	6.	6.	6.	6.	5.	5.	5.	5.	4.	4.	3.	3.	2.	2.	1.	0.	0.	0.	0.
37.5	8.	9.	9.	9.	9.	9.	8.	8.	8.	7.	7.	6.	6.	5.	4.	4.	3.	2.	1.	0.	0.	0.	0.
33.0	13.	14.	13.	13.	13.	12.	11.	11.	11.	10.	10.	8.	7.	6.	5.	5.	3.	2.	2.	1.	0.	0.	0.
29.0	21.	21.	20.	20.	19.	18.	17.	16.	15.	13.	12.	11.	9.	8.	6.	5.	4.	3.	2.	1.	0.	0.	0.
25.5	36.	36.	35.	33.	30.	27.	24.	22.	20.	18.	16.	14.	11.	9.	7.	6.	4.	3.	2.	1.	0.	0.	0.
22.5	71.	71.	68.	62.	55.	46.	39.	33.	28.	23.	20.	16.	13.	11.	8.	6.	4.	3.	2.	1.	0.	0.	0.
19.5	157.	156.	145.	127.	105.	85.	67.	53.	41.	33.	25.	20.	16.	12.	9.	7.	5.	3.	2.	1.	0.	0.	0.
17.0	280.	278.	256.	224.	188.	149.	114.	83.	61.	45.	32.	23.	18.	14.	10.	7.	5.	4.	2.	1.	0.	0.	0.
15.0	422.	421.	392.	347.	290.	227.	174.	124.	86.	61.	40.	26.	20.	15.	11.	8.	6.	4.	2.	1.	0.	0.	0.
13.0	607.	604.	567.	505.	423.	336.	253.	178.	121.	80.	50.	31.	22.	16.	11.	8.	6.	4.	3.	1.	0.	0.	0.
11.0	866.	862.	805.	710.	601.	486.	368.	256.	168.	109.	63.	36.	24.	17.	12.	8.	6.	4.	3.	1.	0.	0.	0.
9.0	1258.	1235.	1136.	1001.	852.	682.	515.	359.	235.	149.	80.	41.	26.	18.	12.	8.	6.	4.	3.	1.	0.	0.	0.
7.0	1759.	1738.	1593.	1384.	1159.	927.	705.	489.	313.	189.	96.	47.	29.	19.	13.	9.	6.	4.	3.	1.	0.	0.	0.
5.0	2382.	2349.	2154.	1843.	1533.	1225.	916.	627.	392.	233.	115.	52.	30.	20.	13.	9.	7.	5.	3.	1.	0.	0.	0.
3.0	3014.	2985.	2756.	2356.	1934.	1519.	1127.	771.	477.	272.	132.	55.	30.	20.	13.	9.	6.	4.	3.	1.	0.	0.	0.
1.0	3513.	3471.	3188.	2723.	2210.	1712.	1264.	853.	524.	302.	139.	56.	31.	20.	13.	9.	6.	4.	3.	1.	0.	0.	0.
0.0	3594.	3552.	3252.	2779.	2253.	1746.	1281.	859.	527.	303.	140.	56.	31.	20.	13.	9.	6.	4.	3.	1.	0.	0.	0.
-1.0	3552.	3508.	3212.	2759.	2238.	1728.	1262.	849.	521.	296.	136.	56.	31.	20.	13.	9.	6.	4.	3.	1.	0.	0.	0.
-3.0	3146.	3119.	2854.	2450.	2015.	1566.	1139.	769.	467.	267.	124.	52.	30.	20.	13.	9.	6.	4.	3.	1.	0.	0.	0.
-5.0	2503.	2482.	2281.	1979.	1638.	1289.	935.	627.	387.	225.	107.	46.	28.	19.	13.	9.	6.	4.	3.	1.	0.	0.	0.
-7.0	1853.	1841.	1702.	1494.	1253.	989.	720.	484.	304.	179.	89.	42.	26.	18.	12.	8.	6.	4.	3.	2.	0.	0.	0.
-9.0	1301.	1291.	1204.	1078.	904.	716.	524.	352.	225.	136.	72.	37.	24.	17.	11.	8.	6.	4.	3.	2.	0.	0.	0.
-11.0	904.	896.	838.	745.	631.	495.	362.	246.	160.	99.	56.	33.	22.	16.	11.	8.	6.	4.	3.	2.	0.	0.	0.
-13.0	617.	609.	568.	503.	423.	328.	238.	166.	112.	73.	45.	28.	20.	15.	10.	7.	6.	4.	3.	2.	0.	0.	0.
-15.0	401.	395.	369.	327.	272.	210.	155.	110.	76.	53.	35.	24.	18.	14.	10.	7.	5.	4.	3.	1.	0.	0.	0.
-17.0	252.	248.	230.	203.	172.	134.	101.	73.	53.	40.	29.	21.	16.	12.	9.	7.	5.	4.	2.	1.	0.	0.	0.
-19.5	135.	134.	127.	112.	93.	76.	60.	46.	36.	29.	23.	18.	14.	11.	8.	6.	5.	3.	2.	1.	0.	0.	0.
-22.5	65.	64.	60.	55.	48.	41.	35.	30.	25.	22.	18.	15.	12.	10.	7.	6.	5.	3.	2.	1.	0.	0.	0.
-25.5	35.	35.	33.	31.	28.	26.	23.	21.	19.	17.	15.	13.	11.	9.	7.	5.	4.	3.	2.	1.	0.	0.	0.
-29.0	21.	21.	20.	20.	18.	18.	16.	15.	14.	13.	11.	10.	9.	7.	6.	5.	4.	3.	2.	1.	0.	0.	0.
-33.0	13.	13.	13.	13.	12.	12.	11.	11.	10.	10.	9.	8.	7.	6.	5.	4.	3.	3.	2.	1.	0.	0.	0.
-37.5	9.	9.	9.	9.	9.	9.	8.	8.	8.	7.	7.	6.	5.	5.	4.	4.	3.	2.	2.	1.	0.	0.	0.
-42.5	5.	6.	5.	6.	6.	6.	6.	6.	5.	5.	5.	4.	4.	4.	3.	3.	2.	2.	1.	1.	0.	0.	0.
-47.5	3.	4.	4.	4.	4.	4.	4.	4.	4.	4.	4.	4.	3.	3.	3.	2.	2.	1.	1.	0.	0.	0.	0.
-55.0	2.	3.	3.	2.	2.	3.	2.	2.	3.	2.	2.	2.	2.	2.	2.	2.	1.	1.	1.	0.	0.	0.	0.
-65.0	1.	2.	1.	1.	1.	1.	1.	1.	2.	1.	1.	1.	1.	1.	1.	1.	1.	0.	0.	0.	0.	0.	0.
-75.0	0.	0.	1.	0.	1.	1.	1.	1.	1.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.
-85.0	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.
-90.0	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.

BEAM EDGE = 1797. CP = 50% OF MAX
 FIELD EDGE = 359. CP = 10% OF MAX



INDEPENDENT TESTING LABORATORIES, INC.
3386 LONGHORN ROAD, BOULDER, CO 80302 USA

PHONE: (303)442-1255 • FAX: (303)449-5274 • E-MAIL: itl@itlboulder.com • WEBSITE: www.itlboulder.com

REPORT NUMBER: ITL63762
PREPARED FOR: B-K LIGHTING, INC.

DATE: 12/29/09
REVISED: 02/01/10

CANDELA TABULATION - FIELD ONLY

PAGE 3

AVERAGE OF RIGHT AND LEFT SIDES

	0.0	1.0	3.0	5.0	7.0	9.0	11.0	13.0	15.0	17.0	19.5	22.5	25.5	29.0	33.0	37.5	42.5	47.5	55.0	65.0	75.0	85.0	90.0	
90.0																								
85.0																								
75.0																								
65.0																								
55.0																								
47.5																								
42.5																								
37.5																								
33.0																								
29.0																								
25.5																								
22.5																								
19.5																								
17.0																								
15.0	422.	421.	392.																					
13.0	607.	604.	567.	505.	423.																			
11.0	866.	862.	805.	710.	601.	486.	368.																	
9.0	1258.	1235.	1136.	1001.	852.	682.	515.																	
7.0	1759.	1738.	1593.	1384.	1159.	927.	705.	489.																
5.0	2382.	2349.	2154.	1843.	1533.	1225.	916.	627.	392.															
3.0	3014.	2985.	2756.	2356.	1934.	1519.	1127.	771.	477.															
1.0	3513.	3471.	3188.	2723.	2210.	1712.	1264.	853.	524.															
0.0	3594.	3552.	3252.	2779.	2253.	1746.	1281.	859.	527.															
-1.0	3552.	3508.	3212.	2759.	2238.	1728.	1262.	849.	521.															
-3.0	3146.	3119.	2854.	2450.	2015.	1566.	1139.	769.	467.															
-5.0	2503.	2482.	2281.	1979.	1638.	1289.	935.	627.	387.															
-7.0	1853.	1841.	1702.	1494.	1253.	989.	720.	484.																
-9.0	1301.	1291.	1204.	1078.	904.	716.	524.																	
-11.0	904.	896.	838.	745.	631.	495.	362.																	
-13.0	617.	609.	568.	503.	423.																			
-15.0	401.	395.	369.																					
-17.0																								
-19.5																								
-22.5																								
-25.5																								
-29.0																								
-33.0																								
-37.5																								
-42.5																								
-47.5																								
-55.0																								
-65.0																								
-75.0																								
-85.0																								
-90.0																								

BEAM EDGE = 1797. CP = 50% OF MAX
FIELD EDGE = 359. CP = 10% OF MAX

THIS REPORT IS BASED ON PUBLISHED INDUSTRY PROCEDURES. FIELD PERFORMANCE MAY DIFFER FROM LABORATORY PERFORMANCE.



INDEPENDENT TESTING LABORATORIES, INC.
 3386 LONGHORN ROAD, BOULDER, CO 80302 USA

PHONE: (303)442-1255 • FAX: (303)449-5274 • E-MAIL: itl@itlboulder.com • WEBSITE: www.itlboulder.com

REPORT NUMBER: ITL63762
 PREPARED FOR: B-K LIGHTING, INC.

DATE: 12/29/09
 REVISED: 02/01/10

LUMEN TABULATION

AVERAGE OF RIGHT AND LEFT SIDES

	0	2	4	6	8	10	12	14	16	18	21	24	27	31	35	40	45	50	60	70	80	90	TOTAL
90	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
80	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
70	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.1
60	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.3
50	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.2
45	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.3
40	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.4
35	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.5
31	0.1	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.6
27	0.1	0.1	0.1	0.1	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.7
24	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.0	0.0	0.1	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.0
21	0.3	0.3	0.2	0.2	0.2	0.1	0.1	0.1	0.1	0.1	0.1	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.8
18	0.3	0.3	0.3	0.2	0.2	0.1	0.1	0.1	0.1	0.1	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.9
16	0.5	0.5	0.4	0.4	0.3	0.2	0.1	0.1	0.1	0.1	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	2.8
14	0.7	0.7	0.6	0.5	0.4	0.3	0.2	0.1	0.1	0.1	0.1	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	4.0
12	1.1	1.0	0.9	0.7	0.6	0.4	0.3	0.2	0.1	0.1	0.1	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	5.6
10	1.5	1.4	1.2	1.0	0.8	0.6	0.4	0.3	0.2	0.1	0.1	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	7.8
8	2.1	1.9	1.7	1.4	1.1	0.8	0.6	0.4	0.2	0.2	0.1	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	10.7
6	2.9	2.6	2.2	1.9	1.5	1.1	0.7	0.5	0.3	0.2	0.1	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	14.1
4	3.6	3.4	2.9	2.3	1.8	1.3	0.9	0.6	0.3	0.2	0.1	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	17.7
2	4.2	3.9	3.3	2.7	2.1	1.5	1.0	0.6	0.4	0.2	0.1	0.1	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	20.1
0	4.3	3.9	3.3	2.7	2.1	1.5	1.0	0.6	0.3	0.2	0.1	0.1	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	20.3
-2	3.8	3.5	3.0	2.4	1.9	1.4	0.9	0.5	0.3	0.2	0.1	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	18.2
-4	3.0	2.8	2.4	2.0	1.6	1.1	0.7	0.5	0.3	0.2	0.1	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	14.7
-6	2.2	2.1	1.8	1.5	1.2	0.9	0.6	0.4	0.2	0.2	0.1	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	11.2
-8	1.6	1.5	1.3	1.1	0.9	0.6	0.4	0.3	0.2	0.1	0.1	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	8.1
-10	1.1	1.0	0.9	0.8	0.6	0.4	0.3	0.2	0.1	0.1	0.1	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	5.7
-12	0.7	0.7	0.6	0.5	0.4	0.3	0.2	0.1	0.1	0.1	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	3.9
-14	0.5	0.4	0.4	0.3	0.3	0.2	0.1	0.1	0.1	0.1	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	2.6
-16	0.3	0.3	0.2	0.2	0.2	0.1	0.1	0.1	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.7
-18	0.2	0.2	0.2	0.2	0.1	0.1	0.1	0.1	0.1	0.1	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.6
-21	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.9
-24	0.1	0.1	0.1	0.1	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.6
-27	0.1	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.6
-31	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.4
-35	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.4
-40	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.3
-45	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.2
-50	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.3
-60	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.1
-70	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
-80	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
-90	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
	35.8	32.9	28.5	23.6	18.6	13.7	9.5	6.1	3.8	3.1	1.7	1.2	1.2	0.8	0.7	0.5	0.3	0.4	0.1	0.0	0.0	0.0	182.6

LUMEN TOTAL THIS PAGE = 182.6



INDEPENDENT TESTING LABORATORIES, INC.
 3386 LONGHORN ROAD, BOULDER, CO 80302 USA

PHONE: (303)442-1255 • FAX: (303)449-5274 • E-MAIL: itl@itlboulder.com • WEBSITE: www.itlboulder.com

REPORT NUMBER: ITL63762
 PREPARED FOR: B-K LIGHTING, INC.


DATE: 12/29/09
 REVISED: 02/01/10

LUMEN TABULATION - FIELD ONLY

AVERAGE OF RIGHT AND LEFT SIDES

	0	2	4	6	8	10	12	14	16	18	21	24	27	31	35	40	45	50	60	70	80	90	TOTAL	
90																							0.0	
80																							0.0	
70																							0.0	
60																							0.0	
50																							0.0	
45																							0.0	
40																							0.0	
35																							0.0	
31																							0.0	
27																							0.0	
24																							0.0	
21																							0.0	
18																							0.0	
16																							0.0	
14	0.5	0.5																					1.0	
12	0.7	0.7	0.6	0.5																			2.6	
10	1.1	1.0	0.9	0.7	0.6	0.4																	4.6	
8	1.5	1.4	1.2	1.0	0.8	0.6																	6.6	
6	2.1	1.9	1.7	1.4	1.1	0.8	0.6																9.7	
4	2.9	2.6	2.2	1.9	1.5	1.1	0.7	0.5															13.3	
2	3.6	3.4	2.9	2.3	1.8	1.3	0.9	0.6															16.8	
0	4.2	3.9	3.3	2.7	2.1	1.5	1.0	0.6															19.3	
-2	4.3	3.9	3.3	2.7	2.1	1.5	1.0	0.6															19.4	
-4	3.8	3.5	3.0	2.4	1.9	1.4	0.9	0.5															17.4	
-6	3.0	2.8	2.4	2.0	1.6	1.1	0.7	0.5															14.1	
-8	2.2	2.1	1.8	1.5	1.2	0.9	0.6																10.3	
-10	1.6	1.5	1.3	1.1	0.9	0.6																	6.9	
-12	1.1	1.0	0.9	0.8	0.6	0.4																	4.8	
-14	0.7	0.7	0.6	0.5																			2.6	
-16	0.5	0.4																					0.9	
-18																							0.0	
-21																							0.0	
-24																							0.0	
-27																							0.0	
-31																							0.0	
-35																							0.0	
-40																							0.0	
-45																							0.0	
-50																							0.0	
-60																							0.0	
-70																							0.0	
-80																							0.0	
-90																							0.0	
	33.9	31.2	26.1	21.5	16.0	11.8	6.5	3.3	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	150.3

LUMEN TOTAL THIS PAGE = 150.3



REPORT NUMBER: ITL63762
PREPARED FOR: B-K LIGHTING, INC.

DATE: 12/29/09
REVISED: 02/01/10

ISOCANDELA CURVES

AVERAGE OF RIGHT AND LEFT SIDES

