



B-K LIGHTING  
 SSL-MR-6-D-AJ  
 CAST METAL HOUSING, FABRICATED DIFFUSE METAL  
 ADJUSTABLE  
 SOCKET MOUNTING BRACKET, MACHINED BLACK  
 PAINTED METAL SOCKET  
 BRACKET MOUNTING RING, CLEAR FLAT LINEAR  
 PRISMATIC GLASS LENS

Horizontal Footcandles  
 Scale: 1 Inch = 4 Ft.  
 Light Loss Factor = 1.00  
 Total Lumens Per Luminaire = 827  
 Mounting Height = 1.50 Ft  
 Maximum Calculated Value = 16.89 Fc  
 Arrangement: Single

PHOTOMETRIC FILENAME : ITL59497.IES

**DESCRIPTIVE INFORMATION (From Photometric File)**

B-K LIGHTING  
SSL-MR-6-D-AJ  
CAST METAL HOUSING, FABRICATED DIFFUSE METAL  
ADJUSTABLE  
SOCKET MOUNTING BRACKET, MACHINED BLACK  
PAINTED METAL SOCKET  
BRACKET MOUNTING RING, CLEAR FLAT LINEAR  
PRISMATIC GLASS LENS

**TEMPLATE SPECIFICATION**

Horizontal Footcandles  
Scale: 1 Inch = 4 Ft.  
Light Loss Factor = 1.00  
Total Lumens Per Luminaire = 827  
Mounting Height = 1.50 Ft  
Maximum Calculated Value = 16.89 Fc  
Arrangement: Single

**LUMINAIRE LAYOUT INFORMATION**

<u>#</u>	<u>X</u>	<u>Y</u>	<u>Z</u>	<u>Orient</u>	<u>Tilt</u>	<u>Roll</u>	<u>Spin</u>	<u>Tilt Correction</u>
1	0.00	0.00	1.50	0.00	0.00	0.00	0.00	1.00