



B-K LIGHTING
 SSL-MR-6-D-AJ
 CAST METAL HOUSING, FABRICATED DIFFUSE METAL
 ADJUSTABLE
 SOCKET MOUNTING BRACKET, MACHINED BLACK
 PAINTED METAL SOCKET
 BRACKET MOUNTING RING, CLEAR FLAT LINEAR
 PRISMATIC GLASS LENS

Horizontal Footcandles
 Scale: 1 Inch = 4 Ft.
 Light Loss Factor = 1.00
 Total Lumens Per Luminaire = 827
 Mounting Height = 1.00 Ft
 Maximum Calculated Value = 36.77 Fc
 Arrangement: Single

PHOTOMETRIC FILENAME : ITL59497.IES

DESCRIPTIVE INFORMATION (From Photometric File)

B-K LIGHTING
SSL-MR-6-D-AJ
CAST METAL HOUSING, FABRICATED DIFFUSE METAL
ADJUSTABLE
SOCKET MOUNTING BRACKET, MACHINED BLACK
PAINTED METAL SOCKET
BRACKET MOUNTING RING, CLEAR FLAT LINEAR
PRISMATIC GLASS LENS

TEMPLATE SPECIFICATION

Horizontal Footcandles
Scale: 1 Inch = 4 Ft.
Light Loss Factor = 1.00
Total Lumens Per Luminaire = 827
Mounting Height = 1.00 Ft
Maximum Calculated Value = 36.77 Fc
Arrangement: Single

LUMINAIRE LAYOUT INFORMATION

<u>#</u>	<u>X</u>	<u>Y</u>	<u>Z</u>	<u>Orient</u>	<u>Tilt</u>	<u>Roll</u>	<u>Spin</u>	<u>Tilt Correction</u>
1	0.00	0.00	1.00	0.00	0.00	0.00	0.00	1.00