



itl boulder
THE LIGHT CENTER OF THE INDUSTRY SINCE 1955

PHONE: (303) 442-1255

FAX: (970) 535-3114

E-MAIL: itl@itlboulder.com

WEBSITE: www.itlboulder.com


NVLAP
NVLAP LAB CODE: 200925-0

INDEPENDENT TESTING LABORATORIES, INC.

4066 CAMELOT CIRCLE, LONGMONT, CO 80504 USA

ISOFOOTCANDLE LINES OF HORIZONTAL ILLUMINATION

Values based on 1 foot mounting height.



REPORT NUMBER: ITL87087-GONIOPHOTOMETRY

ISSUE DATE: 03/24/16 PAGE: 1 OF 8

PREPARED FOR: B-K LIGHTING, INC.

CATALOG NUMBER: CD-SS-LED-e66-A

LUMINAIRE: MACHINED CYLINDRICAL METAL HOUSING, ONE BLACK CIRCUIT BOARD WITH 3 LEDS, ONE CLEAR CONICAL PLASTIC OPTIC PER LED WITH FROSTED SURFACE OPPOSITE LED, MOLDED BLACK PLASTIC OPTIC MOUNTING FRAME, CLEAR FLAT LINEAR PRISMATIC GLASS LENS, CAST BLACK PAINTED METAL FACEPLATE, LENS PRISMS OUT AND VERTICAL.

LAMPS: THREE WHITE LIGHT EMITTING DIODES (LEDs), AIMED AT THE HORIZON.

INPUT ELECTRICAL: 12.0 VOLTS, 6.37

WATTS, 0.591 AMPS

LED DRIVER: B-K LIGHTING 524438/400188-L, DRIVER HAS MULTIPLE LEADS, ONLY LINE INPUT AND LED OUTPUT LEADS CONNECTED FOR THIS TEST.


NOTE: DATA SHOWN IS ABSOLUTE FOR THE SAMPLE PROVIDED AT RATED INPUT VOLTAGE (12VAC, 60Hz) TO THE DRIVER.

POTENTIOMETER ON THE LED CIRCUIT BOARD SET TO POSITION "9" FOR THIS TEST.

TEST PROCEDURE: IESNA LM-79-08


TEST DISTANCE = 20.0 FEET

IES Cutoff Classification: Noncutoff



Checked B. HYRE

Approved R. BEATTIE
Lighting Engineer



itl boulder
THE LIGHT CENTER OF THE INDUSTRY SINCE 1955

NVLAP
NVLAP LAB CODE: 200925-0

INDEPENDENT TESTING LABORATORIES, INC.
4066 CAMELOT CIRCLE, LONGMONT, CO 80504 USA

PHONE: (303) 442-1255 • FAX: (970) 535-3114 • E-MAIL: itl@itlboulder.com • WEBSITE: www.itlboulder.com

REPORT NUMBER: ITL87087-GONIOPHOTOMETRY

ISSUE DATE: 03/24/16 PAGE: 2 OF 8

PREPARED FOR: B-K LIGHTING, INC.

CATALOG NUMBER: CD-SS-LED-e66-A

LUMINAIRE: MACHINED CYLINDRICAL METAL HOUSING, ONE BLACK CIRCUIT BOARD WITH 3 LEDS, ONE CLEAR CONICAL PLASTIC OPTIC PER LED WITH FROSTED SURFACE OPPOSITE LED, MOLDED BLACK PLASTIC OPTIC MOUNTING FRAME, CLEAR FLAT LINEAR PRISMATIC GLASS LENS, CAST BLACK PAINTED METAL FACEPLATE, LENS PRISMS OUT AND VERTICAL.

LAMPS: THREE WHITE LIGHT EMITTING DIODES (LEDs), AIMED AT THE HORIZON.

INPUT ELECTRICAL: 12.0 VOLTS, 6.37 WATTS, 0.591 AMPS

LED DRIVER: B-K LIGHTING 524438/400188-L, DRIVER HAS MULTIPLE LEADS, ONLY LINE INPUT AND LED OUTPUT LEADS CONNECTED FOR THIS TEST.


NOTE: DATA SHOWN IS ABSOLUTE FOR THE SAMPLE PROVIDED AT RATED INPUT VOLTAGE (12VAC, 60Hz) TO THE DRIVER.

POTENTIOMETER ON THE LED CIRCUIT BOARD SET TO POSITION "9" FOR THIS TEST.

TEST PROCEDURE: IESNA LM-79-08

TEST DISTANCE = 20.0 FEET

MAXIMUM PLANE AND MAXIMUM CONE PLOTS OF CANDELA






REPORT NUMBER: ITL87087-GONIOPHOTOMETRY
ISSUE DATE: 03/24/16
PREPARED FOR: B-K LIGHTING, INC.

PAGE: 3 OF 8


COEFFICIENTS OF UTILIZATION AND FLUX DISTRIBUTION



	LUMENS	PERCENT OF FIXTURE
DOWNWARD STREET SIDE	30.1	98.8
DOWNWARD HOUSE SIDE	0.4	1.2
DOWNWARD TOTAL	30.4	100.0
UPWARD STREET SIDE	0.0	0.0
UPWARD HOUSE SIDE	0.0	0.0
UPWARD TOTAL	0.0	0.0
TOTAL FLUX	30.5	100.0

EFFICACY = 4.8 lm/W

ALL CANDELA AND LUMENS IN THIS REPORT ARE BASED ON ABSOLUTE PHOTOMETRY.
THE COEFFICIENT OF UTILIZATION VALUES ARE BASED ON THE TOTAL ABSOLUTE
LUMEN OUTPUT OF THIS LUMINAIRE SAMPLE.



itl boulder
THE LIGHT CENTER OF THE INDUSTRY SINCE 1955

PHONE: (303) 442-1255 • FAX: (970) 535-3114 • E-MAIL: itl@itlboulder.com • WEBSITE: www.itlboulder.com



INDEPENDENT TESTING LABORATORIES, INC.
4066 CAMELOT CIRCLE, LONGMONT, CO 80504 USA

REPORT NUMBER: ITL87087-GONIOPHOTOMETRY
ISSUE DATE: 03/24/16
PREPARED FOR: B-K LIGHTING, INC.

PAGE: 4 OF 8

FLUX DISTRIBUTION BY SOLID ANGLE

(PER IESNA TM-15-11, LUMINAIRE CLASSIFICATION
SYSTEM FOR OUTDOOR LUMINAIRES)

	LUMENS	PERCENT OF FIXTURE	BUG ZONE RATINGS
FORWARD LIGHT	30.1	98.8	
FL (0- 30)	0.5	1.6	
FM (30- 60)	5.1	16.7	
FH (60- 80)	22.3	73.1	G0
FVH(80- 90)	2.2	7.3	G0
BACK LIGHT	0.4	1.2	
BL (0- 30)	0.3	0.9	B0
BM (30- 60)	0.1	0.3	B0
BH (60- 80)	0.0	0.0	B0 G0
BVH(80- 90)	0.0	0.0	G0
UPLIGHT	0.0	0.0	
UL (90-100)	0.0	0.0	U1
UH (100-180)	0.0	0.0	U0
TRAPPED LIGHT	0.0	0.0	
TOTAL FLUX	30.5	100.0	

BACKLIGHT, UPLIGHT, AND GLARE (BUG) RATINGS
(PER ADDENDUM A FOR IESNA TM-15-11)

BUG RATING: B0 U1 G0



itl boulder
THE LIGHT CENTER OF THE INDUSTRY SINCE 1955

NVLAP
NVLAP LAB CODE: 200925-0

INDEPENDENT TESTING LABORATORIES, INC.
4066 CAMELOT CIRCLE, LONGMONT, CO 80504 USA


PHONE: (303) 442-1255 • FAX: (970) 535-3114 • E-MAIL: itl@itlboulder.com • WEBSITE: www.itlboulder.com

REPORT NUMBER: ITL87087-GONIOPHOTOMETRY
ISSUE DATE: 03/24/16
PREPARED FOR: B-K LIGHTING, INC.

PAGE: 5 OF 8

CANDELA TABULATION

STREET SIDE		LATERAL ANGLE										
		0.0	5.0	15.0	25.0	35.0	45.0	55.0	65.0	75.0	85.0	90.0
	180.0	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.
	175.0	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.
	165.0	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.
	155.0	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.
	145.0	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.
	135.0	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.
	125.0	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.
	115.0	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.
	105.0	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.
	95.0	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.
	92.5	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.
	90.0	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.
	87.5	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.
	85.0	7.	8.	6.	4.	2.	1.	0.	0.	0.	0.	0.
V	82.5	25.	24.	19.	12.	6.	2.	1.	0.	0.	0.	0.
E	80.0	48.	46.	36.	23.	11.	3.	1.	1.	0.	0.	0.
R	77.5	70.	68.	53.	33.	15.	5.	1.	1.	0.	0.	0.
T	75.0	86.	83.	68.	45.	21.	7.	1.	1.	0.	0.	0.
I	72.5	101.	98.	79.	49.	23.	7.	2.	1.	0.	0.	0.
C	71.0<<	104.	101.	78.	47.	22.	7.	2.	1.	0.	0.	0.
A	70.0	102.	99.	75.	45.	21.	7.	2.	1.	0.	0.	0.
L	67.5	89.	86.	64.	39.	18.	6.	2.	1.	0.	0.	0.
	65.0	70.	68.	52.	32.	16.	6.	2.	1.	0.	0.	0.
A	62.5	53.	51.	40.	25.	13.	5.	2.	1.	0.	0.	0.
N	60.0	39.	38.	30.	20.	11.	4.	1.	1.	0.	0.	0.
G	57.5	28.	28.	23.	15.	8.	3.	1.	1.	0.	0.	0.
L	55.0	21.	21.	17.	11.	7.	3.	1.	1.	0.	0.	0.
E	52.5	16.	16.	13.	9.	5.	3.	1.	1.	0.	0.	0.
	50.0	13.	13.	11.	7.	4.	2.	1.	1.	0.	0.	0.
	47.5	11.	11.	9.	6.	4.	2.	1.	1.	0.	0.	0.
	45.0	9.	9.	7.	5.	3.	2.	1.	1.	0.	0.	0.
	42.5	7.	7.	6.	4.	3.	2.	1.	1.	0.	0.	0.
	40.0	6.	6.	5.	4.	3.	2.	1.	1.	0.	0.	1.
	37.5	5.	5.	4.	3.	2.	2.	1.	1.	1.	1.	1.
	35.0	4.	4.	3.	3.	2.	2.	1.	1.	1.	1.	1.
	30.0	3.	2.	2.	2.	2.	1.	1.	1.	1.	1.	1.
	25.0	2.	2.	2.	2.	1.	1.	1.	1.	1.	1.	1.
	20.0	1.	1.	1.	1.	1.	1.	1.	1.	1.	1.	1.
	15.0	1.	1.	1.	1.	1.	1.	1.	1.	1.	1.	1.
	10.0	1.	1.	1.	1.	1.	1.	1.	1.	1.	1.	1.
	5.0	1.	1.	1.	1.	1.	1.	1.	1.	1.	1.	2.
	0.0	1.	1.	1.	1.	1.	1.	1.	1.	1.	1.	1.
		PLANE OF MAXIMUM CANDELA										
		CONE OF MAXIMUM CANDELA										



itl boulder
THE LIGHT CENTER OF THE INDUSTRY SINCE 1955



INDEPENDENT TESTING LABORATORIES, INC.
4066 CAMELOT CIRCLE, LONGMONT, CO 80504 USA

PHONE: (303) 442-1255 • FAX: (970) 535-3114 • E-MAIL: itl@itlboulder.com • WEBSITE: www.itlboulder.com

REPORT NUMBER: ITL87087-GONIOPHOTOMETRY
ISSUE DATE: 03/24/16
PREPARED FOR: B-K LIGHTING, INC.

PAGE: 6 OF 8

CANDELA TABULATION

	HOUSE SIDE	LATERAL ANGLE									
		95.0	105.0	115.0	125.0	135.0	145.0	155.0	165.0	175.0	180.0
	180.0	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.
	175.0	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.
	165.0	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.
	155.0	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.
	145.0	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.
	135.0	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.
	125.0	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.
	115.0	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.
	105.0	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.
	95.0	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.
	92.5	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.
	90.0	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.
	87.5	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.
	85.0	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.
V	82.5	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.
E	80.0	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.
R	77.5	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.
T	75.0	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.
I	72.5	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.
C	71.0<<	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.
A	70.0	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.
L	67.5	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.
	65.0	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.
A	62.5	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.
N	60.0	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.
G	57.5	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.
L	55.0	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.
E	52.5	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.
	50.0	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.
	47.5	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.
	45.0	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.
	42.5	1.	0.	0.	0.	0.	0.	0.	0.	0.	0.
	40.0	1.	1.	0.	0.	0.	0.	0.	0.	0.	0.
	37.5	1.	1.	0.	0.	0.	0.	0.	0.	0.	0.
	35.0	1.	1.	0.	0.	0.	0.	0.	0.	0.	0.
	30.0	1.	1.	1.	0.	0.	0.	0.	0.	0.	0.
	25.0	1.	1.	1.	0.	0.	0.	0.	0.	0.	0.
	20.0	1.	1.	1.	1.	0.	0.	0.	0.	0.	0.
	15.0	1.	1.	1.	1.	1.	1.	0.	0.	0.	0.
	10.0	1.	1.	1.	1.	1.	1.	1.	1.	1.	1.
	5.0	1.	1.	1.	2.	1.	1.	1.	1.	2.	1.
	0.0	1.	1.	1.	1.	1.	1.	1.	1.	1.	1.

CONE OF MAXIMUM CANDELA



INDEPENDENT TESTING LABORATORIES, INC.
4066 CAMELOT CIRCLE, LONGMONT, CO 80504 USA

PHONE: (303) 442-1255 • FAX: (970) 535-3114 • E-MAIL: itl@itlboulder.com • WEBSITE: www.itlboulder.com

REPORT NUMBER: ITL87087-GONIOPHOTOMETRY
ISSUE DATE: 03/24/16
PREPARED FOR: B-K LIGHTING, INC.

PAGE: 7 OF 8

5-DEGREE
ZONAL LUMEN SUMMARY

0- 5	0.0
5- 10	0.1
10- 15	0.1
15- 20	0.1
20- 25	0.2
25- 30	0.2
30- 35	0.3
35- 40	0.4
40- 45	0.5
45- 50	0.8
50- 55	1.2
55- 60	2.1
60- 65	3.8
65- 70	6.1
70- 75	7.3
75- 80	5.2
80- 85	2.0
85- 90	0.2
90- 95	0.0
95-100	0.0
100-105	0.0
105-110	0.0
110-115	0.0
115-120	0.0
120-125	0.0
125-130	0.0
130-135	0.0
135-140	0.0
140-145	0.0
145-150	0.0
150-155	0.0
155-160	0.0
160-165	0.0
165-170	0.0
170-175	0.0
175-180	0.0

10-DEGREE
ZONAL LUMEN SUMMARY

0- 10	0.1
0- 20	0.4
0- 30	0.8
0- 40	1.4
0- 50	2.7
0- 60	5.9
0- 70	15.8
0- 80	28.2
0- 90	30.4
0-100	30.5
0-110	30.5
0-120	30.5
0-130	30.5
0-140	30.5
0-150	30.5
0-160	30.5
0-170	30.5
0-180	30.5



itl boulder
THE LIGHT CENTER OF THE INDUSTRY SINCE 1955



INDEPENDENT TESTING LABORATORIES, INC.
4066 CAMELOT CIRCLE, LONGMONT, CO 80504 USA

PHONE: (303) 442-1255 • FAX: (970) 535-3114 • E-MAIL: itl@itlboulder.com • WEBSITE: www.itlboulder.com

REPORT NUMBER: ITL87087-GONIOPHOTOMETRY
ISSUE DATE: 03/24/16
PREPARED FOR: B-K LIGHTING, INC.

PAGE: 8 OF 8

ADDRESS: 40429 BRICKYARD DRIVE
MADERA, CA 93636-9515

THIS ITL REPORT WITH THE USE OF THE NVLAP LOGO SHALL NOT BE USED BY THE CLIENT TO CLAIM PRODUCT CERTIFICATION, APPROVAL, OR ENDORSEMENT BY NVLAP, NIST, OR ANY AGENCY OF THE FEDERAL GOVERNMENT.