



UL LLC
1075 W Lambert Rd Suite B
Brea, CA 92821

In-Situ Test Report

Relevant Standards
IES LM-79-2008, ANSI C82.77-2002, UL 1598-2008

Prepared For
B-K LIGHTING INC

DANIEL CARREJO
40429 BRICKYARD DR.
MADERA, CA 93636-9515
UNITED STATES

Catalog Number
AP-LED-C26-SP-12-2700K, SM-AP-LED-C26-SP-12-2700K

Order Number

12498468

Test Number

12498468.02A

Revised:

2018-11-19

Test Date

2018-11-15

Prepared By

Luis Torres, Technician

Approved By

Eric Gaudreau, Engineering Leader

The results contained in this report pertain only to the tested sample.
This report shall not be reproduced, except in full, without written approval of Underwriters Laboratories.
This report must not be used by the client to claim product certification, approval, or endorsement by
NVLAP, NIST, or any agency of the Federal Government.



Luminaire Description: White cylindrical metal housing with metal mounting plate; specular prismatic reflector and glass prismatic lens
Lamp: One (1) Luminetix CTM1C19 16-80K 2000L 35W 24V module with diffuse lens and specular reflector
Mounting: Surface – Wall
Ballast/Driver: One (1) Efore Strato RSLP070-24

Luminaire



Summary of Results

LED Temperature: 41.0 °C
Driver Temperature: 54.3 °C

Test Conditions

Test Temperature: 24.0 °C
Voltage: 120.0 VAC
Frequency: 60 Hz

Temperatures are offset to an ambient temperature of 25 °C as described in UL 1598-2008



In-Situ Test

In-Situ Test Conditions

Temperature	Voltage	Current	Power	Power Factor	Frequency	Current THD
24.0 °C	120.0 VAC	N/A	N/A	N/A	60 Hz	N/A


Summary of Results

LED Temperature: 41.0 °C


Driver Temperature: 54.3 °C

Temperatures are offset to an ambient temperature of 25°C as described in UL1598-2008

LED Temperature Location



Thermocouple Reference



Driver Temperature Location

