



UL LLC
1075 W Lambert Rd Suite B
Brea, CA 92821

Integrating Sphere Test Report

Relevant Standards
IES LM-79-2008, ANSI C82.77-2002, CIE 13.3-1995
CIE 15-2004, ANSI C78.377-2017, IES TM-30-2015

Prepared For
B-K Lighting Inc

Daniel Carrejo
40429 Brickyard Dr
Madera, CA 93636-9515
United States

Catalog Number
K2-LED-C26-SP-12-2700K

Order Number

12496739

Test Number

12496739.01A

Revised:

2018-11-19

Test Date

2018-11-09

Prepared By

Austin Duff, Technician

Approved By

Eric Gaudreau, Engineering Leader

The results contained in this report pertain only to the tested sample.
This report shall not be reproduced, except in full, without written approval of Underwriters Laboratories.
This report must not be used by the client to claim product certification, approval, or endorsement by
NVLAP, NIST, or any agency of the Federal Government.



Luminaire Description: White cylindrical metal housing with specular prismatic reflector and glass prismatic lens
Lamp: One (1) Lumenetix CTM1C19 16-80K 2000L 35W 24V Module with diffuse lens and specular reflector
Mounting: Pendant
Ballast/Driver: One (1) EFORE RSLP070-24

Luminaire



Summary of Results

Radiant Flux:	2917 mW
Luminous Flux:	932.3 lm
Luminaire Efficacy:	36.8 lm/W
CCT:	2715 K
CRI (Ra):	95.5
Chromaticity (x):	0.4601
Chromaticity (y):	0.4132
Chromaticity (u):	0.2615
Chromaticity (v):	0.3523
Duv:	0.0006

Test Conditions

Test Temperature:	25.1 °C
Voltage:	120.1 VAC
Current:	0.2196 A
Power:	25.36 W
Power Factor:	0.962
Frequency:	60 Hz
Current THD:	19.7 %

Testing was performed in a 2-meter integrating sphere using the 4 π geometry method.
Absorption correction was employed for this measurement.





Color Quality - Integrating Sphere

Integrating Sphere Test Conditions

Temperature	Voltage	Current	Power	Power Factor	Frequency	Current THD
25.1 °C	120.1 VAC	0.2196 A	25.36 W	0.962	60 Hz	19.7 %

Summary of Results

Total Output:	932 Lumens	Chromaticity (x):	0.4601
Efficacy:	36.8 lm/w	Chromaticity (y):	0.4132
CCT:	2715 K	Chromaticity (u'):	0.2615
CRI (Ra):	95.5	Chromaticity (v'):	0.5284
CRI (R9):	99.2	TM-30 Rf:	91.9
Peak Wavelength:	639 nm	TM-30 Rg:	103.3
Dominant Wavelength:	584 nm	Duv:	0.0006
S/P Ratio:	1.27		



Color Rendering Index Detail

Ra (CRI)	R1	R2	R3	R4	R5	R6	R7	R8	R9	R10	R11	R12	R13	R14	R15
95.5	97.8	95.8	90.0	95.7	96.8	95.2	95.9	96.8	99.2	88.3	95.6	88.3	96.7	93.0	97.7

